

# Airbi HOME—weather station with 3 wireless transmitters

## Key properties

- Temperature and humidity measurement: indoor unit and 3 wireless sensors (max. range 100 m)
- Temperature and humidity trend indicators
- Temperature alarms, frost alarm
- Comfort indicator (smiley face)
- Weather forecast
- Atmospheric pressure measurement, pressure history, graph
- Absolute or relative pressure
- Radio-controlled DCF clock
- Date
- Day abbreviation (7 languages: CZ, SK, PL, HUN, DUT, GER, and ENG)
- alarm clock, 2 alarm times, snooze function
- color display with 3 brightness levels or backlight off
- automatic display dimming function at a set time, e.g. at night
- USB-C power supply (included)
- for hanging on the wall or standing on the table



## Product description

Airbi HOME is a weather station that comes with **3 sensors included**. The sensors have a maximum transmission range of 100 m, and each sensor displays its data in a dedicated segment on the screen. **Waterproof cable probes** are available as **optional accessories**.

The weather station features a high-quality color display that shows not only temperature and humidity, but also **weather forecasts**, **pressure data** with history, **time**, **date**, and **day of the week abbreviation** (available in 7 languages: CZ, SK, PL, HUN, DUT, and more). Time is automatically synchronized via **DCF radio signal**. The base unit includes an **alarm clock** with snooze function, allowing you to set 2 different alarm times.

Standard features include also **comfort indicators** for temperature and humidity (smiley face icons), **trend indicators**, **temperature alarms**, and **frost warning**.

## Technical parameters

### Indoor unit

Power supply	USB-C, 3x of 1.5 V AAA batteries (batteries are not included) (No permanent backlight in pure battery operation.)
Temperature range	-9,9... +50 °C (14,1...122 °F)
Temperature accuracy	±1 °C (at 0...+40 °C, otherwise ±2 °C)
Humidity range	20...95 % rH (outside the measurement range, 20 or 95 % is displayed)
Humidity accuracy	±5 % rH (at 30...80 % rH)
Pressure range	600...1100 hPa
Dimensions	205 x 131 x 26 mm

Weight	317 g (device only)
<b>Wireless temperature and humidity transmitter</b>	
Max. range	100 m
Transmission frequency	433 MHz
Power supply	2× AAA 1.5 V batteries (not included)
Temperature range	-40°C...+60°C (-40...+140 °F)
Temperature accuracy	±1°C (at 0...+40°C, otherwise ±2 °C)
Humidity range	±5 % rH (at 30...80 % rH)
Humidity accuracy	20...95 % rH (outside the measurement range, 20 or 95 % is displayed)
Dimensions	57 x 106 x 27 mm
Weight	57 g (device only)

## Gallery



## Delivery contents

- Base station
- USB-C cable, power adapter
- 3x temperature and humidity sensor
- Instruction manual

## Accessories

- BI1013 – Waterproof cable probe [EAN: 8594162601264]

## Documents

- [User manual](#)

### Logistics information

Product code: BI1032

Country of origin: China

EAN code: 8594162601240

Customs code (TARIC/HS): 90258040

	Number pcs	Mass (kg)	Width (cm)	Depth (cm)	Height (cm)
Product		0.32	20.5	2.6	13.1
Product packaging		0.67	21.5	8.6	14.0
Carton with products	10	7.20	45.5	23.0	30.5